

ES Antikor SL

Special alloy

Tensile strength:

approx. 950-1100 N/mm²

Characteristic or application:

this newly developed special material is a further development of the well-known steel ES Antikor S.

| Thickness in mm | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 |
|-----------------|------|------|------|------|------|------|------|------|------|------|
| | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 | 500 |
| | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 |
| | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | 2000 | | |

| Thickness in mm | 120 | 130 | 140 | 150 | 160 | 170 | 180 | 190 | 205 | 225 |
|-----------------|------|------|------|------|------|------|------|------|------|------|
| | 500 | 500 | 500 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 |
| | 1010 | 1010 | 1010 | | | | | | | |

| Thickness in mm | 235 | 245 | 255 | 275 | 305 | 325 | 355 | 375 | 405 |
|-----------------|------|------|------|------|------|------|------|------|------|
| | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 | 1010 |

We can saw from larger stock to meet your particular dimensional requirements at short notice.